

Ultra R SIP Walls & Roof Shell Materials - Appendix A



Wall Envelope: R-Control Structural Insulated Wall Panels (SIP) 7/16" OSB, EPS Core, 7/16" OSB 2" x 6" Corner, Window, Door Bucks and Plates 6 1/2" R-Control R-Value 22.6@75 degrees and 24.3@40 degrees R-Control Structural Insulated Wall Panels (SIP) 7/16" OSB, EPS Core, 7/16" OSB 2" x 6" Corner, Window, Door Bucks and Plates PerformGuard Termite Protection FrameGuard Mold & Mildew Warranty Delamination Warrantees Energy Star Approved LEEDApproved US Green Building Council Approved Underwriters Certificate of Testing ICC-ES-ESR-2233 Code Compliance Splines, Low voc Sealant, Big Red screws, R-Control SIP Tape Green Guard House Wrap Wire chases per specifications * <i>PFS third party QC for Code Compliance</i> * <i>Penn Industrial Housing components Approval</i> First Floor System Sill Seal and 2"x 8" PT Sill Plate Metal Posts with Top & Bottom Plates 2" x 10"/ 12" Joists Perimeter w/Metal Bridging 3/4" T&G Advantech Sub floor	 ol Structural Insulated Wall Panels (SIP) OSB, EPS Core, 7/16" OSB Graner, Window, Door Bucks and Plates Gaud degrees R-Control Structural d Wall Panels (SIP) SB, EPS Core, 7/16" OSB Corner, Window, Door Bucks and Plates Guard Termite Protection uard Mold & Mildew Warranty ation Warrantees Structural Ridge & Purlins as engineered R-Control Structural Insulated Roof Panels Roof 10 1/4" R-Control R-Value 37@.75 deg and 39.9@40degrees 7/16" OSB EPS Core, 7/16" OSB Corner, Window, Door Bucks and Plates Guard Termite Protection uard Mold & Mildew Warranty ation Warrantees EsR-2233 Code Compliance Low voc Sealant, Big Red screws, ol SIP Tape uard House Wrap ases per specifications <i>ird party QC for Code Compliance</i> <i>Penn Industrial Housing components Approval</i> neluty Carry Beams 12" Joists Perimeter w/Metal Bridging Advantech Sub floor Floor System: 		 Porch Deck 6" x 6" PT (2') Pier Posts Built-up PT Carry Beams 2" x 6"/8" PT Joists, Ledger and Trim Aluminum Drip Cap and Joist Hangers 5/4"x 6" PT Decking Plus: CODE REQUIRED Deck Attachment Materials for Lateral Loads Simpson HTT4 Plates Simpson LV26 Joist Hangers 5/8" Diameter Rod Hold-Down or Similar Tension device Porch Roof 6" x 6" Posts (surfaced) 6" x 8" Carry Beams (surfaced) 2" x 8" Rafters 2" x 6" Ceiling Joists 1" KD V-Groove White Pine Ceiling 5/8" T&G OSB Sheathing (or Fir w/H clips) Roofing as above Garage Sill Seal and PT Sill Plate 2" x 4" Framing/Top and Bottom Plates 7/16" OSB Wall & Gable Sheathing 2" x 12" Built-up Garage Door Headers Standard & Gable Trusses/Bracing 5/8" T&G OSB Sheathing (or Fir w/H clips) Roofing as above
2" x 10"/12" Joists Perimeter with Metal Bridging 3/4" Advantech T&G Subfloor Note:All material not listed is to be provided by others	Crockett Standard Building Plans Code compliant for banks and permits. FOB Crockett Mills 1/2015 Engineers Stamp Crockett Construction Guidelines		Note: Garage Doors (by others)
		Date:	
Model Name: Package Price \$ Additions: \$		Special Notes:	
\$ Deletions: \$ \$		Buyer:	Date:
Total\$Tax:\$Stotal Price:\$Good for 30 DaysPrice is exclusive of labor, shipping and taxesShipping Estimate \$		Seller:	Date:

Crockett offers a full range of options. Crockett invites all custom design projects for free written pricing. Prices do not include labor, shipping and/or taxes. Materials are FOB Crockett Distribution Centers. Crockett Log & Timber Homes reserves the right to make changes without notice in price, materials and specifications. Phone: 1-800-566-7714 • www.crockettloghomes.com • Email: jdodson@crockettloghomes.com Copyright 2015 Crockett Log & Timber Homes